CK-Series







Version: 1.20



CK-Series Feature Guide

- □ 1/6000 Resolution, Legal for Trade Approval #03-011
- □ Stainless Steel platter and ABS plastic sub-platter
- Ultra Quick-Response Weight display
- □ Portable design: easily used in any location
- Tough high quality UV-sealed keypad
- Compact medium-sized footprint design

- □ Capacities: 12 x 0.002 lb / 30 x 0.005 lb / 60 x 0.01 lb
- □ Pole display models: CK-P12, CK-P30, & CK-P60
- User-friendly PLU programming
- Quick operation keypad for high throughput
- □ Function keys: 4 PLUs, Save, Tare, and Zero
- External AC adapter with long power cord





Technical Specifications

recinical specifications					
Models:	CK-12 & CK-P12	CK-30 &	CK-P30	CK-60 & CK-P60	
Capacity and Graduation:	12 x 0.002 lb	30 x 0.005 lb		60 x 0.01 lb	
Maximum Tare:	12 lb	30 lb		60 lb	
NTEP Certificate Number:	Approved 1/6000 resolution, Legal for Trade, CC #03-011				
A/D Conversion Rate:	50 Updates / second				
Direct PLU Keys:	4 Direct PLU keys which can be programmed with Tares and Unit Prices				
Liquid Crystal Displays (LCD):	Weight: 6 Digits,	999.999 max	(
	Unit Price: 6 Digits, 9999.99 max				
	Total Price: 6 Digits,	9999.99 max	(
Platter Size:	Width: 300 mm / 11.8"				
	Length: 225 mm / 8.9"				
Accreditation:	NTEP Class III, OIML, CE, ISO 9002				
Product Dimensions:	CK-12, CK-30, CK	-60	CK-P12	, CK-P30, CK-P60	
	Width: 320 mm / 12	.6"	Width:	320 mm / 12.6"	
	Length: 340 mm / 13	.4"	Length:	340 mm / 13.4"	
	Height: 125 mm / 4.5	5"	Height:	575 mm / 22.6"	
AC Adapter Specifications:	AC Input: 120 Volts AC @ 60 Hz, DC Output: 9 Volts DC, 800mA, Positive Tip				
Battery Specifications:	100 hours without backlight / 48 hours with backlight (Continuous use.)				
Power Consumption & Fuse Rating:	Approximately 10 Watts / Fuse: 250 Volts, 1.5 Amp, 20 mm				

Options

☐ Foreign Power Adapter: 220 Volts AC @ 50 Hz	☐ Fish Tray Optional Platter
□ Cigarette Lighter Car Adapter	Wet-Proof Protective Overlay

Acom America Inc. 404 Paulding Ave. Northvale, New Jersey 07647 Tel: (201) 750-9900 Fax: (201) 750-7100





call:561-582-5510 email:info@cashregisterservices.net

*NOTE: Specifications are subject to change without notice.